







COLT'S PT. R. HARTFORD CT. U.S.A.

HUNTSMAN

COLT AUTOMATIC  
CAL. 22 LONG RIFLE

















COLT AUTOMATIC  
CAL. 22 LONG RIFLE



















COLT





**HUNTSMAN  
AUTOMATIC PISTOL**

18

**22** LONG RIFLE

**6** INCH BBL.

**COLT  
BLUE**




183883-C



**WARRANTY**

We hereby warrant this Colt Firearm to be free from defects in material and workmanship under normal use and service for a period of 12 months from the date of purchase. Colt's obligation is limited to repairing or replacing, F.O.B. Hartford, Conn., U.S.A., any part of a Colt's Firearm which Colt's examination discloses to be thus defective.

This warranty is in lieu of all other warranties, expressed or implied. This warranty shall not apply to defects resulting from accidents, alterations or misuse. If, in the opinion of Colt's gunsmiths employed at Hartford, Connecticut, modifications or changes have affected the operation of the weapon to render it faulty, this warranty shall be void. This warranty shall also be void if any part not of Colt's manufacture has been incorporated, or if other than factory loaded ammunition is fired in it.

Colt Industries  **Colt's Firearms Division**  
 HARTFORD, CONNECTICUT, U.S.A. 06102

## COLT'S HUNTSMAN AUTOMATIC PISTOL

**ACTION** The action of this pistol is automatic only in the sense that after firing, the spent shell is extracted from the chamber and a new cartridge is stripped from the magazine and fed into the chamber. The trigger must be pulled to fire each shot. The disconnecting mechanism which prevents full automatic action as in a machine gun also prevents firing the pistol if the slide is not fully closed.

**SAFETY LOCK** The safety lock, when pushed up, locks the slide from moving back and the sear from moving out from under the

The brass wire brush should be dipped in the cleaning fluid and the barrel cleaned with wire out with catches.

**ASSEMBLY • DISASSEMBLY • MAGAZINE • CLEANING**



**DUALTONE FINISH** To minimize accuracy-disturbing glare, all reflecting areas have a glass-protect "satin" finish, with other areas retaining the regular, high polish, Colt Blue.

The magazine has an easily operable thumb-piece which facilitates loading. The magazine is held in the receiver by a magazine catch located at base of main spring housing. Thumb pressure on this catch releases the magazine.